Coastal Structure Risk and Reliability

Lajes, Azores Breakwater

US Army Corps of Engineers

Jeffrey A. Melby, PhD
Leader, Coastal Structures Group

Coastal and Hydraulics Laboratory - ERDC

Outline

- Types of coastal structures
- Asset management initiatives
- Risk and reliability overview for coastal structures
  - Loads and Responses
  - Failure modes
  - Reliability methods and tools available
  - Life-cycle analysis method
- Example



Structure Type and Function

Breakwater

Wave Protection, Sediment Control

St. Paul, Alaska



Neah Bay, Washington

US Army Corps of Engineers

Coastal and Hydraulics Laboratory - ERDC

Structure Type and Function

Breakwater

Redondo Beach, CA, Breakwater
1988, 60-year storm

Kahului, Hawaii

Buffalo, New York

US Army Corps of Engineers

Coastal and Hydraulics Laboratory - ERDC

Structure Type and Function

Jetty

Sediment control and wave re

Umpqua, Oregon

Ocean City Inlet, Maryland



Newport, Oregon

US Army Corps of Engineers

Coastal and Hydraulics Laboratory - ERDC

Structure Type and Function

Revetment

Shore Protection

Structure Type and Function

Levee, Groin, Seawall, Caisson

Coastal Structure Asset Management Initiatives



CIRP Asset Mgt Work Unit

Nav Sys program and MCR, Katrina, Chesapeake DDI, Neah Bay projects

Nav Sys and MNCP Programs – R&D work units, MCNP work units, District surveys

eCoastal GIS definitions, data, tools

US Army Corps of Engineers

Coastal and Hydraulics Laboratory - ERDC

Risk and Reliability Overview

- Forcing: Waves and water levels at structure toe (No earthquake and Tsunami)
- Response: Empirical equations for armor instability, wave overtopping, …

Failure Modes



Risk and Reliability Overview

Failure Modes

Identify applicable limit states and construct event tree

Example of Failure Function

Hudson Equation for armor stability

$$\frac{H_s}{\Delta D_n} = (K_D \cot \alpha)^{1/3}$$

Armor Instability on Crest Hinge

Risk and Reliability Overview

Limit State Equations

$$g = \overbrace{\Delta\, D_n \left(K_D \cot\alpha\right)^{1/3}}^{\text{Resistance}} - \overbrace{H_s}^{\text{Loading}} \qquad \begin{cases} < 0 & \text{failure} \\ = 0 & \text{limit state} \\ > 0 & \text{no failure} \end{cases}$$

Some resistance and loading variables are stochastic.
g can be represented as a probability distribution.

Definitions:

Probability of Failure $P_f = \text{Prob}\left[\, g \leq 0 \,\right]$

Reliability $R_f = 1 - P_f$

During a reference period (i.e., return period)

Risk and Reliability Overview

Probabilistic Design Levels

- **Level I:** Deterministic-type design formula with probability-based safety factors → CEM
- **Level II:** Simplified computation of reliability index – approximate failure surface at design point using Taylor series → CEM, CEDAS
- **Level III:** Actual distributions of stochastic variables are applied or computed ex. Monte Carlo simulations → EST, @RISK

Life Cycle Analysis

CEM Chapter V-1 "The life cycle approach deals with multiple realizations of possible evolution of the project with time during the span of its design life. The suite of life cycle realizations is constructed with consideration of the probabilities of key variables."

Can't do life cycle analysis without damage function

Life Cycle Analysis

Goals

- Minimum p.w. cost of varied alternatives
- Safety level or probability of exceeding various limit states
- Impact of repair policy (Cost, environmental, downtime, catastrophic damage)



Storm Suite Simulation

- Monte Carlo from theoretical extremal distributions
- EST - Empirical Simulation Technique
- WELS – Wave/Water Level Empirical Life Cycle Simulation
  - Simulate future times series statistically similar to past
  - Avoids complex fitting to theoretical distributions
  - Time dependent
  - Maintains complex nonlinear correlations between many parameters
  - Reproduces phase related information - slowly varying storm intensity (El Nino)

Poplar Island, Chesapeake Bay





James Island

Barren Island

US Army Corps of Engineers

Coastal and Hydraulics Laboratory - ERDC

Project Objectives

- Dredge disposal site
- Retain clean dredge material
- Restore eroded island
- Establish natural island habitat for birds, fish, etc.
- Low maintenance



Unarmored Crest Alternative



Armored Crest Alternative



Historical Waves

Hindcast 150 years of waves and water levels and transformed waves for 39 stations - Look at Station 33



Poplar Island

Wave/Water Level Empirical Life Cycle Simulation

Cumulative Distributions - Historical and WELS







Wave Height, Hs

Peak Wave Period, Tp

Water Level, h

US Army Corps of Engineers

Coastal and Hydraulics Laboratory - ERDC

Limit States or Failure Modes

Identify limit states, performance functions, and construct fault tree or event tree



Damage Classes

Initial damage: S = 0 - 2

Intermediate damage: S = 2 – 12 (used S=8)

Breach Failure: Underlayer exposed S = 8-20 (used S=18)



Empirical Life-Cycle Simulation

Preliminary Analyses

Hindcast historical waves and water levels and transform waves to representative stations – WIS, WISWAVE, STWAVE, ADCIRC, CEDAS

Determine extremal wave statistics for 5 –100 year return periods - CEDAS

Simulate future wave and water level climates – EST, WELS

Determine input variable ranges, repair rules, unit costs, fixed costs, extraneous costs of repair

Cross-Section Design

Design structure cross-section at each station for various return periods

Determine initial quantities and

Cross-Section Analysis

Step through time series of wave and water level determining eroded area, runup, overtopping, transmission

Accumulate damage and check against repair rules

Repair if required and sum PW costs

Accumulate all present worth costs

Output individual and total stats

Programs LC-COST-REV and LC-COST-BW

Damage Accumulation and Repair History



Major Maintenance

Number of Breaches due to Armor Instability



Station 33
Total Cost





Unarmored Crest

Armored Crest

Number of Repairs





Summary

- ELS - risk analysis methodology
- Time series simulation
- Incorporate time dependent phenomenon into design process
- Useful for rubble mound structure design/optimization
- Minimize overall project costs and unexpected maintenance or environmental/collateral damages

Sunrise at Duck, NC